



DQ6.6

HIGH VOLTAGE STORAGE BATTERY



- 6.62kWh capacity
- Scalable to 92.68kWh
- 95% Depth of Discharge
- Large temperature tolerance
- CAN communication



HIGH
VOLTAGE



EASY
INSTALLATION



HIGH
EFFICIENCY



EXPANDABLE
SYSTEM



95%
DOD

The DQ6.6 is a high-performance, scalable battery storage system. The modular design allows for maximum flexibility, making it suitable for a broad range of storage applications.

Additional batteries can be installed in series, allowing for a maximum storage capacity of 92.68kWh. Installation is easy, with a plug and play solution that can save valuable time for installers.



For more information about the Fox ESS range, visit:
www.fox-ess.com



TECHNICAL SPECIFICATIONS

MODEL	DQ6.6												
	-L2 (w)	-L3 (w)	-L4 (w)	-L5 (w)	-L6 (w)	-L7 (w)	-L8 (w)	-L9 (w)	-L10 (w)	-L11 (w)	-L12 (w)	-L13 (w)	-L14 (w)
ELECTRICAL CHARACTERISTICS													
Battery Type	LFP (LiFePO ₄)												
Battery Module [DQ6.6-M (w)]	1												
Battery Module [DQ6.6-S (w)]	1	2	3	4	5	6	7	8	9	10	11	12	13
Nominal Energy [kWh]	13.24	19.86	26.48	33.10	39.72	46.34	52.96	59.58	66.20	72.82	79.44	86.06	92.68
Nominal Voltage [V]	115.2	172.8	230.4	288.0	345.6	403.2	460.8	518.4	576.0	633.6	691.2	748.8	806.4
Operating Voltage [V]	104.4 ~ 919.8												
Nominal Capacity [Ah]	115												
Recommend Charge/Discharge Current [A]	50												
Max. Charge/Discharge Current [A]*1	80												
Peak Discharge Current [A]	110 @60sec												
Battery Pack Round-Trip Efficiency [%]*2	>95												
Depth of Discharge [%]	95												
Communication	CAN												
Display	DQ6.6-S (w): LED*1, DQ6.6-M (w): LED*6												
Scalability	Max. 14 Modules in Series												
OPERATING CONDITIONS													
Installation Location	Outdoor/ Indoor (Stand)												
Operating Temperature [°C] (warm up function off)	Charge: 0 ~ 55, Discharge: -10 ~ 55												
Operating Temperature [°C] (warm up function on)	Charge: -25 ~ 55, Discharge: -25 ~ 55												
Storage Temperature [°C]	-10 ~ 50												
Cooling Method	Natural Convection												
Humidity [%]	5 ~ 95 (No Condensation)												
Altitude [m]	Max. 3,000												
PROTECTION													
Fire Protection Function	YES												
MECHANICAL CHARACTERISTICS													
Dimensions (W*D*H) [mm]	660*360												
	*420	*575	*730	*885	*1040	*1195	*1350	*1505	*1660	*1815	*1970	*2125	*2280
Weight [kg] (±5%)	102.8	151.6	200.4	249.2	298.0	346.8	395.6	444.4	493.2	542.0	590.8	639.6	688.4
CERTIFICATES													
Safety	IEC 62619												
EMC	IEC 61000-6-1/2/3/4												
Transportation	UN38.3												
Ingress Protection	IP65												

*1, The current is affected by temperature, cell voltage and SOC.
*2 @25°C, 0.3C charging/discharging.